

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 771 572 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
07.05.1997 Bulletin 1997/19

(51) Int Cl.⁶: A61M 25/01

(21) Application number: 96307820.9

(22) Date of filing: 29.10.1996

(84) Designated Contracting States:
CH DE ES FR GB IT LI NL SE

(72) Inventor: Lorenzo, Juan
Miami, Florida 33185 (US)

(30) Priority: 30.10.1995 US 550532

(74) Representative: Mercer, Christopher Paul
Carpmaels & Ransford
43, Bloomsbury Square
London WC1A 2RA (GB)


(71) Applicant: Cordis Corporation
Miami Lakes Florida 33014 (US)

(54) Guidewire with radiopaque markers

(57) The guidewire comprises: a tip section including a core wire including a first tapered portion, a reduced-in-diameter portion, a second tapered portion and a rod end portion, two or more highly radiopaque

annular marker bands being received on the core wire between the first tapered portion and the rod end portion and precisely spaced apart on the core wire by one or more plastic tubing segments, and an outer sleeve covering said marker bands and tubing segments.

FIG. 1



EP 0 771 572 A1

Description

The present invention relates to a guidewire assembly with radiopaque markers which are defined by highly radiopaque, bands or coils made of a suitable radiopaque material, such as, platinum iridium, platinum nickel or platinum tungsten and are spaced apart predetermined distances by plastic, e.g. polyimide, tubing segments located in a tip section of the guidewire assembly.

Heretofore numerous guidewires have been proposed with radiopaque markers. Examples of these previously proposed guidewires with marker bands are disclosed in the following prior art U.S. and foreign patents:

U.S. Patent No.	Patentee
3,706,883	McIntyre
4,884,579	Engelson
4,922,924	Gambale et al.
5,063,935	Gambale
5,144,959	Gambale et al.
5,174,302	Palmer
5,213,111	Cook et al.
5,253,653	Daigle et al.
5,259,393	Corso, Jr. et al.
5,267,574	Viera et al.
5,353,808	Viera
5,402,799	Colon et al.
5,406,960	Corso, Jr.

Foreign Publications:

WO 93/08862	Daigle, et al.
-------------	----------------

The patents referred to above disclose various forms of marker bands that are provided in a guidewire.

For example, the Daigle et al. U.S. Patent No. 5,253,653 discloses radiopaque rings which serve as markers which are mounted on a necked down portion of a core wire just proximal to a tip of a guidewire. The markers are held to the smaller diameter section of the guidewire by an adhesive, welding, soldering or brazing. In one embodiment the markers are interspersed between coil segments of a coiled wire.

The use of radiopaque coils interspersed between nonradiopaque coils in a coiled wire guidewire is disclosed in the Palmer U.S. Patent No. 5,174,302.

As will be described in greater detail hereinafter, in the guidewire assembly of the present invention, highly radiopaque marker bands are spaced apart predetermined distances on a cylindrical portion of a core wire or on a tapered portion of a core wire by plastic, e.g. polyimide, tubing segments having predetermined precise lengths and with the bands and tubing segments having a polytetrafluorethylene sleeve thereover.

SUMMARY OF THE INVENTION

According to the present invention there is provided a guidewire comprising: a tip section including a core wire including a first tapered portion, a reduced-in-diameter portion, a second tapered portion and a rod end portion, two or more highly radiopaque annular marker bands being received on the core wire between the first tapered portion and the rod end portion and precisely spaced apart on the core wire by one or more plastic tubing segments, and an outer sleeve covering the marker bands and tubing segments.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a longitudinal sectional view of a guidewire assembly with radiopaque markers constructed according to the teachings of the present invention.

FIG. 2 is an enlarged, fragmentary, longitudinal sectional view of a radiopaque coil wire segment precisely located between two polyimide tubing segments.

FIG. 3 is an enlarged, fragmentary, longitudinal sectional view of a radiopaque band precisely located between two polyimide tubing segments.

DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

Referring now to the drawings in greater detail, there is illustrated in Fig. 3 a longitudinal sectional view of a tip section 10 of a guidewire 12 having highly radiopaque markers 14 which can be defined by platinum iridium, platinum nickel or platinum tungsten coiled wire segments 21-26 precisely spaced apart by a plurality, e.g. five or more, polyimide tubing segments 31-37 mounted on a stainless steel core wire 40 which includes a primary body portion 42 having a polytetrafluorethylene coating 44 thereon, a slightly reduced in-diameter portion 46, a first tapered portion 48, a more reduced-in-diameter portion 50, a second tapered portion 52 tapering down to an end rod portion 54 that extends to and is connected to the distal tip 56 of the core wire 40.

Typically, nine (9) marker bands 14 are used separated by ten (10) tubing segments.

Each marker band 14 can be 1 mm to 3 mm with 1.5 mm being a preferred width W for each band 14.

Each tubing segment spacer 31, 32 and 33 has a width L between 5mm and 20mm with 1 cm being a preferred width L. One or more segments, e.g. segment 34, can be 4 cm.

A platinum tungsten coiled wire 58, which is fused or welded to the distal tip 56 of the core wire 40, extends proximally to a necked down coiled wire portion 60 that ends in a reduced-in-diameter proximal coiled wire portion 62 that is received over the end rod portion 54 and held thereto by a heat shrunk polytetrafluorethylene sleeve 64 that is heat shrunk over the proximal coiled wire portion 62, the tubing segments 31-37 and the high-

ly radiopaque, e.g., platinum iridium, coil wire segments 21-26. The sleeve 64 extends proximally from the proximal coiled wire portion 62 to the slightly reduced-in-diameter portion 46.

The radiopaque coil wire segments 21-26 can be made of a platinum alloy including 90% platinum and 10% iridium. Alternatively, solid bands 70 (FIG. 3) of 90% platinum and 10% iridium material can be used in place of coiled wire segments 21-26.

While polyimide is a preferred plastic for the tubing segments 31-37, other plastics can be utilized including polyurethane and polyvinylchloride (PVC).

According to the teachings of the present invention, the first three tubing segments 31-33 each have a length of approximately 1cm whereas the tubing segment 34 has a length of approximately 4cm. The segments 31-37 can be between 1cm and 8cm.

One, namely coiled wire segment 24 of the radiopaque coiled wire segments 21-26, is shown in an enlarged view in FIG. 2 spaced between tubing segments 34 and 33.

As shown in FIG. 3, the radiopaque 70 can be utilized in place of the radiopaque coiled wire segments 21-26.

The use of the tubing segments or spacers 31-37 interspersed between radiopaque coiled wire segments or bands 21-27 or 70, provides for a tip section 10 in a guidewire 12 which has highly radiopaque markers 14 (21-27 or 70) spaced apart by highly non-radiopaque tubing segments 31-37 thereby to provide a tip section 10 with highly visible radiopaque markers 14 (21-27 or 70) precisely spaced apart within the tip section 10 of the guidewire 12.

From the foregoing description, it will be apparent that the tip section 10 of the guidewire 12 constructed according to the teachings of the present invention has a number of advantages, some of which have been described above and others of which are inherent in the invention. For example, the spacers 31-37 and marker bands 14 provide a continuous surface whereby the outer surface of sleeve 21 is smooth without bumps. Also, modifications can be made to the tip section 10 having radiopaque markers 14 and tubing segments 31-37 without departing from the teachings of the invention. For example, spacers 31 and 37 can be omitted. Accordingly the scope of the invention is only to be limited as necessitated by the accompanying claims.

Claims

1. A guidewire comprising: a tip section including a core wire including a first tapered portion, a reduced-in-diameter portion, a second tapered portion and a rod end portion, two or more highly radiopaque annular marker bands received on said core wire between said first tapered portion and said rod end portion and precisely spaced apart on

said core wire by one or more plastic tubing segments, and an outer sleeve covering the marker bands and tubing segments.

2. The guidewire of claim 1 wherein said annular marker bands are made of platinum iridium, platinum nickel or platinum tungsten.
3. The guidewire of claim 1 or claim 2 wherein said annular marker bands are made of platinum iridium solid annular bands or coiled wire segments.
4. The guidewire of any one of claims 1 to 3 wherein said tubing segments are made of polyimide.
5. The guidewire of any one of claims 1 to 4 wherein said outer sleeve is made of polytetrafluorethylene.
6. The guidewire of any one of claims 1 to 5 wherein three marker bands are spaced apart by two plastic tubing segments each having a length between approximately 5mm and 20mm.
7. The guidewire of claim 6 wherein said length is approximately 10mm.
8. The guidewire of claim 6 or claim 7 wherein the proximal one of the three marker bands is spaced apart by a plastic tubing segment having a length of approximately 1cm to 8cm from the next proximal marker band.
9. The guidewire of any one of claims 1 to 8 including between 2 to 15 marker bands.
10. The guidewire of any one of claims 1 to 9 wherein said core wire is made of stainless steel.

FIG. 1




FIG. 2





FIG. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 7820

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL.6)
A	WO 95 24237 A (BARD) * page 7, paragraph 3 - page 13, paragraph 2; figures 1,2 *	1-3,10	A61M25/01
D,A	US 5 267 574 A (VIERA) * column 4, line 22 - line 37; figure 4 *	1-3,5	
A	US 5 084 022 A (CLAUDE) * abstract; figures *	1,10	
D,A	US 5 253 653 A (DAIGLE) * abstract; figures *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int. CL.6) A61M
Place of search THE HAGUE		Date of completion of the search 28 January 1997	Examiner Kousouretas, I
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background U : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (01.01.1997)